

@ i a]bU]fY' 7 cbghf i Wh]cb

7B7' a UW\]bYX'Zfc a 'cbY'cZ'h\Y'
Zc`ck]b[' a YhU'g

7cddYf

Body: 45.4mm (1¾") Copper rod.
Pole: 38mm (1½") x 850mm
(33½") Copper tube.

'%*' GhU]b`Ygg` GhYY'

Body; 45.4mm (1¾") Stainless
Steel rod.
Pole: 38mm (1½") x 850mm
(33½") Stainless Steel tube.

FYhfc i

Pole: 38mm (1½") x 410mm (16")
tube.
Driver Pole: 63.5mm (2½") x
440mm (17½") tube.

@ i a]bU]fY' KY][\h

12volt Cop 1.900kg (4lb 3oz)
SS 1.550kg (3lb 6oz)

Retro™ Cop 2.800kg (6lb 2oz)
SS 2.600kg (5lb 11oz)

@ i a]bU]fY' :YUh i fYg

@Ybg

6mm (¼") extra clear low iron flush
fit shatter resistant glass.
Lifetime Warranty.

; Ug_Yh

Silicone, iron impregnated 220°C
(428°F)

5WYyggcf]Yg

Cable Joint Kit (Cat. CJK150)
Frosted Euro Lens (Cat. EURF)

Gk]jY'g

Copper luminaires - 360° rotation
and 0-90° elevation, solid brass with
anti rust spring.

Stainless Steel luminaires - 360°
rotation and 0-90° elevation, full
stainless steel construction.

Ac i bh]b['

Pole 850mm (31½") directly mount-
ed into the earth.
Retro™ - set in concrete.

Technical Information

Standards

AS/NZS 61046
IP67 UL 1838

LED

Cree MTG-2 Plug and Play, field
replaceable LED board.

Lumen Output: 420 at 700mA
Lumens Per watt: 105 minimum
CRI Warm White (3000k): 85+
Colour Temp: 2700K, 3000K and
4000K

<][\ ' 7 F:' Cdh]cb' fl' \$\$\$?L. 90+
(lumen output decreases by 15%)

DckYf`Gi dd`m

9 IhYfbU`'flGYf]Ygk' 8f]jYf

Constant current driver
Output: 6vdc at 700mA maximum

=bhY [fU`'%&` Jc`h' 8f]jYf

Hunza™ Plug and Play Driver
Input: 12vac, 5watt total
Output: 6vdc nominal, 350 / 700mA


HfUbgZcf a Yf

Hunza™ Wall Mount Transformer
for use with integral 12v driver


FYhfc`%%\$#&(\$`Jc`h' 8f]jYf

Hunza™ Retro Driver
Input: 120/240vac, 5watt total
Output: 6vdc, 700mA
0-10 volt dimming
(USA - non dimming)


Reflector Beam Angles



15° Angle
3000 K



25° Angle
3000 K



38° Angle
3000 K