

Luminaire Construction

CNC machined from one of the following metals:
 Body: High corrosion resistant low copper 63.5mm (2½") x 10mm (25/64") aluminium.
 End cap - solid aluminium 63.5mm (2½") rod.
 Base & Mounting Plate (Retro™): Cast from virgin high corrosion resistant CC401 low copper aluminium alloy chromate substrate and high UV resistant polyester powder coat - Black, Bronze, Green, Silver Star, White, Birch, Dark Grey, Olive Green, Beige, Primrose.

Body: Copper 63.5mm (2½") x 10mm (25/64). End cap - solid copper 63.5mm (2½") rod.
 Base: Copper Hand spun 2mm (5/64").
 Mounting Plate: Forged brass (Retro™).
 Body: 316 Stainless Steel 63.5mm (2½") x 10mm (25/64) rod. End cap - 316 stainless steel 63.5mm (2½") rod.
 Base: Investment cast and CNC machined.
 Mounting Plate: Investment cast and CNC machined (Retro™).

Mounting


12 volt: the luminaire is mounted to the wall using two 316 stainless screws through a shallow base 16mm (5/8") in depth. A Wall Box Adaptor Plate is available as an accessory to fit 3.0 and 4.0 junction boxes for USA /Canada.
 Retro™ luminaire (110/240-12 volt): a mounting plate is fixed to the wall using two screws and then the luminaire is fitted to the mounting plate.

Features










Lenses:
 7mm (¼") thick clear tempered shatter resistant glass.
Lifetime Warranty .
Gaskets:
 Silicone, iron impregnated 220°C (428°F).
Lamp Holders:
 GU5.3 & GU10 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.

Accessories:
 Cable Joint Kit (Cat. CJK150) Not approved for USA /Canada.
 Frosted Lens (Cat. LENSSTEPF).
 Hex Cell Louvre Adaptor (Cat. HCL).
 Retro™ transformer 110/240-12 volt (Cat. /R).
 Wall Box Adaptor Plate (Cat. WBAP 12 volt luminaire USA /Canada).
 GU10 Option (Cat. GU).
Swivel:
 Aluminium and Copper luminaires - 360 degree rotation and 0 - 90 degree elevation,
 solid brass with anti rust spring.
 Stainless Steel luminaires - 360 rotation and 0 - 90 elevation, full stainless steel construction.

Standards

IP66 AS/NZS61046  UL1838
Luminaire Weight
 12 volt Alum .775kg (1lb 1 1oz)
 Cop 2.230kg (4lb 14oz)
 SS 1.750kg (3lb 13oz)
 Retro™ Alum 1.100kg (2lb 6oz)
 Cop 2.650kg (5lb 13oz)
 SS 2.200kg (4lb 13oz)
Power Supply
 12 volt
 HUNZA™ Inground or HUNZA™ Wall Mount Transformer: not included.
 USA and Canada:
 HUNZA™ Wall Mount Transformer: not included.
 RETRO™
 HUNZA™ 110/240-12 volt ac potted electronic transformer built into the Retro™ base. Dimmable with a suitable dimmer (halogen only).
Luminaire: supplied with
 MR16 GU5.3 2 x 20, 35 watt lamp max.
 GU10 - GU10 25 or 35 watt lamps max.

 USA and Canada:
 MR16 GU5.3 2 x 20 watt lamp max.
 When glare guard fitted lamp wattage can be increased to 35 watt.
 GU10 Halogen - Lamps not supplied



HUNZA™ PURE OUTDOOR LIGHTING

HUNZA FACTORY
 130 Felton Mathew Ave
 Glen Innes
 Auckland 1072
 New Zealand

Ph: 64-9-528 9471
 Fax: 64-9-528 9361
 hunza@hunza.co.nz
 www.hunzalighting.com

INTERNATIONAL CONTACTS:
<http://www.hunzalighting.com/contact.php>

Specifications may change without notice.
 Manufactured in New Zealand. Ver 1.4
 © 2016 Hunza Holdings Ltd.